



# PRIDE 14 / 17

FLUSH MOUNT CEILING

location:  
**DAMP**

## SPECIFICATIONS:

### DESCRIPTION

Flush-mounted ceiling fixture, featuring an drum-shaped Opal Matte Diffuser.

### LAMPING

**Pride 14:** 17W integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 1200 lumens, 25,000 hours, included.

**Pride 17:** 23W integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 2065 lumens, 25,000 hours, included.

### DIFFUSER

Handcrafted of glass in inner Opal Matte.

**Pride 14:** 13.75" Dia. x 3.5" H

**Pride 17:** 16.75" Dia. x 3.75" H

### CONSTRUCTION

Glass diffuser is secured to fitter with "twist & lock" bayonet action. Stamped aluminum fitter is powder coated white.

### MOUNTING


Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.

### LABELS


UL or ETL Listed. Suitable for Damp Locations (interior use only).



OPAL MATTE (PRIDE1407C)



FIXTURE	-	LAMP OPTIONS
PRIDE1407C Opal Matte		LED 17W LED 1200 lumens



FIXTURE	-	LAMP OPTIONS
PRIDE1707C Opal Matte		LED 23W LED 2065 lumens

**Ex. PRIDE1407C-LED**  
Pride 14 Ceiling, Opal Matte Shade

**Project Information:**

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.