



Features

- Can be recessed or surface mounted
- Made of lightweight high quality aluminum
- Frosted lens protects light source while evenly diffusing light
- Field cuttable extrusion and lenses
- Additional focusing lens available for 10° beam pattern control
- Optional end caps and mounting clips available
- Compatible with most Trulux Tape Light

Available Lengths

39-3/8" (1 meter)

Available Finishes



Anodized Aluminum

Compatible Tape Light

- Trulux Single Color
- Trulux Tunable CCT (excludes Double Row)
- Trulux RGB

TRULUX™ Universal Extrusion


The rectangular profile of the Universal Extrusion requires a 5/8" wide by 1/2" deep channel if you recess mount it. It's also suitable for surface mount applications. Use either a UVLENS for general diffusion or a focusing lens for a narrow, focused beam. E-CLIPs are recommended for most surface applications.

Best suited applications:

Stairs, handrails, display shelving and cases, niche and accent lighting

Ordering Information

PE-AA2-1M	Universal Aluminum Extrusion
PE-UVLENS-1M	Frosted Polycarbonate UV Lens
PE-FOCLENS-1M	Beam Angle Focusing Lens (10° with Universal)
PE-AA2-END	Universal End Cap
E-CLIP	Surface Mount Clip



Focusing Lens



Surface Mount Clip